LIVE12



12″ | 1″ | AB AMP* | ANALOG PROC* | 80°x60° | RIGGING | DEDICATED PRESET**

LIVE12A

Active loudspeaker, AB-class bi-amp, 2-way 330W+70W, 124dB SPL

- Low frequency:12 ″ woofer/3″v.c.
- High frequency:1 ″ driver/1.7″v.c.
- Frequency response:50-18000 Hz (±3dB)
- Reproduction of voice and music for live and recorded performances
- Polypropylene enclosure, designed for stage-monitor application
- For indoor/outdoor sound installations where quality and sound pressure are required
- For portable PA systems, mobile DJ sets and voice/multimedia applications

LIVE12

2-way passive loudspeaker, 300W AES, 129dB SPL

- Low frequency:12 ″ woofer/3″v.c.
- High frequency:1 ″ driver/1.7″v.c.
- Frequency response:55-18000 Hz (±3dB)
- Reproduction of voice and music for live and recorded performances
- Polypropylene enclosure, designed for stage-monitor application
- For indoor/outdoor sound installations where quality and sound pressure are required
- For portable PA systems, mobile DJ sets and voice/multimedia applications

LIVE12A TECHNICAL DATA

LOUDSPEAKERS
- System type: active 2 way

COMPONENTS
- Low frequency: 12″ woofer/3″v.c.
- High frequency: 1″ driver/1.7″v.c.

FEATURES
- Built-in amp LF/HF: 330+70W /4/8Ohm
- SPL max: 128dB @1m (free field)

ACOUSTICAL SPECIFICATIONS
- SPL cont/peak: 122/128dB @1m (free field)
- Frequency response: 50-18000Hz (±3dB)
- Coverage angle HxV: 80x60°
- Cross over frequency: 2200Hz

ELECTRONICS
- Amplifier: AB class
- Power: 330+70W /4/8Ohm
- Input sensitivity: -2 dBu (0,6Vrms) adjustable
- Protection: limiter temp.
- User controls: mic, line, master, eq LF-HF
- Processor: analog
- Operating voltage/frequency: 100~120V/220~240V 60Hz/50Hz

INPUT/OUTPUT CONNECTORS
- Input signal: XLR IN/OUT, jack 6.35 mm
- Power connection: VDE

CABINET CONSTRUCTION
- Cabinet material: 4mm polypropilene
- Sospension system: eyebolt, 35 mm pole mount
- Angle: 45° monitor applications
- Handles: 1 on side

PHYSICAL
- Dimensions (WxHxD): 416x615x356mm
- Weight: 25.5kg

LIVE12 TECHNICAL DATA

LOUDSPEAKERS
- System type: passive 2 way

COMPONENTS
- Low frequency: 12″ woofer/3″v.c.
- High frequency: 1″ driver/1.7″v.c.

FEATURES
- AES/program power: 300/600W
- SPL max: 129dB @1m (free field)

ACOUSTICAL SPECIFICATIONS
- Sensitivity: 98dB @1W/1m (free field)
- Impedence: 8
- SPL cont/peak: 123/129dB @1m (free field)
- Frequency response: 55-18000Hz (±3dB)
- Coverage angle HxV: 80x60°
- Cross over frequency: 2000Hz
- Protection: H.F. signal compression
- Recommended amplifier up to: 600W /8Ohm

INPUT/OUTPUT CONNECTORS
- Input signal: 4pole IN/OUT

CABINET CONSTRUCTION
- Cabinet material: 4mm polypropilene
- Sospension system: eyebolt, 35 mm pole mount
- Angle: 45° monitor applications
- Handles: 1 on side

PHYSICAL
- Dimensions (WxHxD): 416x615x365mm
- Weight: 21kg

active version only
****passive version only***

LIVE15



15″ | 1″ | AB AMP* | ANALOG PROC* | 80°x60° | RIGGING | DEDICATED PRESET**

LIVE15A

Active loudspeaker, AB-class bi-amp, 2-way 380W+70W, 124dB SPL

- Low frequency:15 ″ woofer/3″v.c.
- High frequency:1 ″ driver/1.7″v.c.
- Frequency response:45-18000 Hz (±3dB)
- Reproduction of voice and music for live and recorded performances
- Polypropylene enclosure, designed for stage-monitor application
- For indoor/outdoor sound installations where quality and sound pressure are required
- For portable PA systems, mobile DJ sets and voice/multimedia applications

LIVE15

2-way passive loudspeaker, 350W AES, 129.5dB SPL

- Low frequency:15 ″ woofer/3″v.c.
- High frequency:1 ″ driver/1.7″v.c.
- Frequency response:50-18000 Hz (±3dB)
- Reproduction of voice and music for live and recorded performances
- Polypropylene enclosure, designed for stage-monitor application
- For indoor/outdoor sound installations where quality and sound pressure are required
- For portable PA systems, mobile DJ sets and voice/multimedia applications

LIVE15A TECHNICAL DATA

LOUDSPEAKERS
- System type: active 2 way

COMPONENTS
- Low frequency: 15″ woofer/3″v.c.
- High frequency: 1″ driver/1.7″v.c.

FEATURES
- Built-in amp LF/HF: 380+70W /4/8Ohm
- SPL max: 128dB @1m (free field)

ACOUSTICAL SPECIFICATIONS
- SPL cont/peak: 122/128dB @1m (free field)
- Frequency response: 45-18000Hz (±3dB)
- Coverage angle HxV: 80x60°
- Cross over frequency: 2600Hz

ELECTRONICS
- Amplifier: AB class
- Power: 380+70W /4/8Ohm
- Input sensitivity: -2 dBu (0,6Vrms) adjustable
- Protection: limiter temp.
- User controls: mic, line, master, eq LF-HF
- Processor: analog
- Operating voltage/frequency: 100~120V/220~240V 60Hz/50Hz

INPUT/OUTPUT CONNECTORS
- Input signal: XLR IN/OUT, jack 6.35 mm
- Power connection: VDE

CABINET CONSTRUCTION
- Cabinet material: 4mm polypropilene
- Sospension system: eyebolt, 35 mm pole mount
- Angle: 45° monitor applications
- Handles: 2 on side

PHYSICAL
- Dimensions (WxHxD): 475x740x400mm
- Weight: 30kg

LIVE15 TECHNICAL DATA

LOUDSPEAKERS
- System type: passive 2 way

COMPONENTS
- Low frequency: 15″ woofer/3″v.c.
- High frequency: 1″ driver/1.7″v.c.

FEATURES
- AES/program power: 350/700W
- SPL max: 129dB @1m (free field)

ACOUSTICAL SPECIFICATIONS
- Sensitivity: 98dB @1W/1m (free field)
- Impedence: 8
- SPL cont/peak: 123/129dB @1m (free field)
- Frequency response: 50-18000Hz (±3dB)
- Coverage angle HxV: 80x60°
- Cross over frequency: 1700Hz
- Protection: H.F. signal compression
- Recommended amplifier up to: 700W /8Ohm

INPUT/OUTPUT CONNECTORS
- Input signal: 4pole IN/OUT

CABINET CONSTRUCTION
- Cabinet material: 4mm polypropilene
- Sospension system: eyebolt, 35 mm pole mount
- Angle: 45° monitor applications
- Handles: 2 on side

PHYSICAL
- Dimensions (WxHxD): 475x740x400mm
- Weight: 25kg

active version only
passive version only