



## DS40TC

Micro speaker with a closed rear cap. Ideal for high-fidelity sound reproduction designed for ceiling mounting.

### LOUDSPEAKERS

- System type: closed enclosure ceiling speaker

### COMPONENTS

- Full range: 4"

### FEATURES

- AES/program power: 3/6W
- Input 100 V: 1.5/3W

### ACOUSTICAL SPECIFICATIONS

- Sensitivity: 90dB @1W/1m (free field)
- Constant voltage: 70/100 V
- Frequency response: 160÷20.000Hz (±3dB)

### INPUT/OUTPUT CONNECTORS

- Input signal: terminal with wire

### PHYSICAL

- Weight: 0.36kg



## DS62T

Ceiling speaker for recessed mounting, ideal for vocal announcements and reproduction of background music in spaces with low ceilings.

### LOUDSPEAKERS

- System type: ceiling speaker

### COMPONENTS

- Full range: 2.5"

### FEATURES

- AES/program power: 3/6W
- Input 100 V: 1.5/3W

### ACOUSTICAL SPECIFICATIONS

- Sensitivity: 91dB @1W/1m (free field)
- Constant voltage: 70/100 V
- Frequency response: 160÷20.000Hz (±3dB)

### INPUT/OUTPUT CONNECTORS

- Input signal: screw terminal

### PHYSICAL

- Weight: 0.43kg



## DS46T

Ceiling speaker for recessed mounting, ideal for vocal announcements and reproduction of background music.

### LOUDSPEAKERS

- System type: ceiling speaker

### COMPONENTS

- Low frequency: 6"
- High frequency: 1"

### FEATURES

- AES/program power: 20/40W
- Input 100 V: 10/20W

### ACOUSTICAL SPECIFICATIONS

- Sensitivity: 92dB @1W/1m (free field)
- Constant voltage: 70/100 V
- Frequency response: 90÷18.000Hz (±3dB)

### INPUT/OUTPUT CONNECTORS

- Input signal: terminal with wire

### PHYSICAL

- Weight: 1.70kg



## DS45T

Ceiling speaker for recessed mounting, ideal for vocal announcements and reproduction of background music.

### LOUDSPEAKERS

- System type: ceiling speaker

### COMPONENTS

- Low frequency: 5"
- High frequency: 1"

### FEATURES

- AES/program power: 10/20W
- Input 100 V: 5/10W

### ACOUSTICAL SPECIFICATIONS

- Sensitivity: 91dB @1W/1m (free field)
- Constant voltage: 70/100 V
- Frequency response: 100÷16.000Hz (±3dB)

### INPUT/OUTPUT CONNECTORS

- Input signal: terminal with wire

### PHYSICAL

- Weight: 1.24kg



## DS67T

Ceiling speaker for recessed mounting, ideal for vocal announcements and reproduction of background music.

### LOUDSPEAKERS

- System type: ceiling speaker

### COMPONENTS

- Low frequency: 6.5"
- High frequency: 1"

### FEATURES

- AES/program power: 10/20W
- Input 100 V: 2.5/5/10W

### ACOUSTICAL SPECIFICATIONS

- Sensitivity: 93dB @1W/1m (free field)
- Constant voltage: 70/100 V
- Frequency response: 60÷20.000Hz (±3dB)

### INPUT/OUTPUT CONNECTORS

- Input signal: terminal with wire

### PHYSICAL

- Weight: 1.42kg



## DS66T

Built-in ceiling loudspeaker, ideal for announcements and background music reproduction.

### LOUDSPEAKERS

- System type: ceiling speaker

### COMPONENTS

- Full range: 6"

### FEATURES

- AES/program power: 6/12W
- Input 100 V: 3/6W

### ACOUSTICAL SPECIFICATIONS

- Sensitivity: 91dB @1W/1m (free field)
- Constant voltage: 70/100 V
- Frequency response: 100÷13.000Hz (±3dB)

### INPUT/OUTPUT CONNECTORS

- Input signal: terminal with wire

### PHYSICAL

- Weight: 0.72kg