

COMPACT66T ■ BK □ WH

2-way Loudspeaker with bracket, 30W/8ohm or 60-30-15W/100V

LOUDSPEAKERS
- System type: passive 2 way

COMPONENTS
- Low frequency: 6.5”
- High frequency: 1.5”

FEATURES
- AES/program power: 60/120W
- Input 100 V: 15-30-60W

ACOUSTICAL SPECIFICATIONS
- Sensitivity: 90dB @1W/1m (free field)
- Impedance: Low impedence 8 Ohm
- Constant voltage: 70/100 V
- Frequency response: 65÷18.000Hz (±3dB)

INPUT/OUTPUT CONNECTORS
- Input signal: screw terminal

PHYSICAL
- Dimensions (WxHxD): 205x344x202mm
- Weight: 3.80kg



COMPACT88T ■ BK □ WH

2-way loudspeaker with bracket, 60W/8ohm or 80-40-20W/100V

LOUDSPEAKERS
- System type: passive 2 way

COMPONENTS
- Low frequency: 8”
- High frequency: 1.5”

FEATURES
- AES/program power: 80/160W
- Input 100 V: 20-40-80W

ACOUSTICAL SPECIFICATIONS
- Sensitivity: 91dB @1W/1m (free field)
- Impedance: Low impedence 8 Ohm
- Constant voltage: 70/100 V
- Frequency response: 60÷18.000Hz (±3dB)

INPUT/OUTPUT CONNECTORS
- Input signal: screw terminal

PHYSICAL
- Dimensions (WxHxD): 261x445x275mm
- Weight: 7.46kg



DS40T

Micro speaker, ideal for high-fidelity sound reproduction designed for ceiling mounting.

LOUDSPEAKERS
- System type: ceiling speaker

COMPONENTS
- Full range: 4”

FEATURES
- AES/program power: 3/6W
- Input 100 V: 1.5/3W

ACOUSTICAL SPECIFICATIONS
- Sensitivity: 90dB @1W/1m (free field)
- Constant voltage: 70/100 V
- Frequency response: 160÷20.000Hz (±3dB)

INPUT/OUTPUT CONNECTORS
- Input signal: terminal with wire

PHYSICAL
- Weight: 0.35kg



DS40TC

Micro speaker with a closed rear cap. Ideal for high-fidelity sound reproduction designed for ceiling mounting.

LOUDSPEAKERS
- System type: closed enclosure ceiling speaker

COMPONENTS
- Full range: 4"

FEATURES
- AES/program power: 3/6W
- Input 100 V: 1.5/3W

ACOUSTICAL SPECIFICATIONS
- Sensitivity: 90dB @1W/1m (free field)
- Constant voltage: 70/100 V
- Frequency response: 160÷20.000Hz (±3dB)

INPUT/OUTPUT CONNECTORS
- Input signal: terminal with wire

PHYSICAL
- Weight: 0.36kg



DS62T

Ceiling speaker for recessed mounting, ideal for vocal announcements and reproduction of background music in spaces with low ceilings.

LOUDSPEAKERS
- System type: ceiling speaker

COMPONENTS
- Full range: 2.5"

FEATURES
- AES/program power: 3/6W
- Input 100 V: 1.5/3W

ACOUSTICAL SPECIFICATIONS
- Sensitivity: 91dB @1W/1m (free field)
- Constant voltage: 70/100 V
- Frequency response: 160÷20.000Hz (±3dB)

INPUT/OUTPUT CONNECTORS
- Input signal: screw terminal

PHYSICAL
- Weight: 0.43kg



DS46T

Ceiling speaker for recessed mounting, ideal for vocal announcements and reproduction of background music.

LOUDSPEAKERS
- System type: ceiling speaker

COMPONENTS
- Low frequency: 6"
- High frequency: 1"

FEATURES
- AES/program power: 20/40W
- Input 100 V: 10/20W

ACOUSTICAL SPECIFICATIONS
- Sensitivity: 92dB @1W/1m (free field)
- Constant voltage: 70/100 V
- Frequency response: 90÷18.000Hz (±3dB)

INPUT/OUTPUT CONNECTORS
- Input signal: terminal with wire

PHYSICAL
- Weight: 1.70kg