PBL6365

63 A 32x32x32 cm



Portable Power distribution box, 63A 5p input plug

Structure:
- IP54 shock resistant, robust and mobile insulated thermoplastic box
- Box dimensions (WxHxD): 32x32x32 cm

Input:
- 63A-5p (3P+N+E) panel mount CEE plug, 400V 50/60Hz IP67, 1pc (code 913315)

Output:
- 32A-5p (3P+N+E) panel mount CEE socket, 400V 50/60Hz IP67, 2pcs (code 912415)

Protection:
- Residual current circuit breaker w overcurrent protection, 4P, 7 mod, 63A, 10kA, 30mA, 1pc
- Magneto-thermic switch (1P+N), 2 modules, 32A/6kA, 2pcs

Tools:
- 4P fuser block, 4 modules, 1pc
- Triple LED indicator, 1 module, colour red, 1pc

PBL6376

63 A 32x32x32 cm



Portable Power distribution box, 63A 5p input plug

Structure:
- IP54 shock resistant, robust and mobile insulated thermoplastic box
- Box dimensions (WxHxD): 32x32x32 cm

Input:
- 63A-5p (3P+N+E) panel mount CEE plug, 400V 50/60Hz IP67, 1pc (code 913315)

Output:
- 32A-3p (1P+N+E) panel mount CEE socket withslim flange, 230V 50/60Hz IP44, 6pcs (code 912423)

Protection:
- Residual current circuit breaker w/ overcurrent protection, 4P, 7 mod, 63A, 10kA, 30mA, 1pc
- Magneto-thermic switch (1P+N), 2 modules, 32A/6kA, 6pcs

Tools:
- 4P fuser block, 4 modules, 1pc
- Triple LED indicator, 1 module, colour red, 1pc

PBL3221

32 A 32x32x32 cm



Portable Power distribution box, 32A 5p input plug

Structure:
- IP54 shock resistant, robust and mobile insulated thermoplastic box
- Box dimensions (WxHxD): 32x32x32 cm

Input:
- 32A-5p (3P+N+E) panel mount CEE plug, 400V 50/60Hz IP44, 1pc (code 912315)

Output:
- 16A-3p (1P+N+E) panel mount CEE socket, 230V 50/60Hz IP44, 3pcs (code 911413)
- 32A-5p (3P+N+E) panel mount CEE socket with slim flange, 400V 50/60Hz IP44, 1pc (code 912425)

Protection:
- Residual current circuit breaker w overcurrent protection, 4P, 7 modules, 32A, 10kA, 30mA, 1pc
- 4P magneto-thermic switch , 4 modules, 32A/6kA, 1pc
- Magneto-thermic switch (1P+N), 2 modules, 16A/4,5kA, 3pcs

Tools:
- 4P fuser block, 4 modules, 1pc
- Triple LED indicator, 1 module, colour red, 1pc

PBL3232

32 A 32x32x32 cm

Portable Power distribution box, 32A 5p input plug

Structure:
- IP54 shock resistant, robust and mobile insulated thermoplastic box
- Box dimensions (WxHxD): 32x32x32 cm

Input:
- 32A-5p (3P+N+E) panel mount CEE plug, 400V 50/60Hz IP44, 1pc (code 912315)

Output:
- 16A-3p (1P+N+E) panel mount CEE socket, 230V 50/60Hz IP44, 6pcs (code 911413)

Protection:
- Residual current circuit breaker w overcurrent protection, 4P, 7 modules,32A,6kA,30mA, 1pc
- Magneto-thermic switch (1P+N), 2 modules, 16A/4.5kA, 6pcs

Tools:
- 4P fuser block, 4 modules, 1pc
- Triple LED indicator, 1 module, colour red, 1pc



PBL3243

32 A 23x29x29 cm

Portable Power distribution box, 32A 5p input plug

Structure:
- IP54 shock resistant, robust and mobile insulated thermoplastic box
- Box dimensions (WxHxD): 23x29x29 cm

Input:
- 32A-5p (3P+N+E) panel mount CEE plug, 400V 50/60Hz IP44, 1pc

Output:
- 32A-3p (1P+N+E) panel mount CEE socket with slim flange, 230V 50/60Hz IP44, 3pcs

Protection:
- Residual current circuit breaker, 1P+N, 2 modules, 16A, 6KA, 30mA, 3pcs
- 4P magneto-thermic switch , 4 modules, 32A/10kA, 1pc



PBE3254

Portable Power distribution box, 32A 5p input plug

Structure:
- IP54 shock resistant, robust and mobile insulated thermoplastic box
- Box dimensions (WxHxD): 19.7x20x19.7 cm

Input:
- 32A-5p (3P+N+E) panel mount CEE plug, 400V 50/60Hz IP44, 1pc
- Cable HO7RN-F 5x6mm - lenght 200 cm

Output:
- 16A-3p (1P+N+E) panel mount CEE socket, 230V 50/60Hz IP44, 6pcs

Protection:
- Magneto-thermic switch 1P, 1 modules, 16A/10kA, 6pcs

