

LUMIPARIRCH
(included)

FLATPAR6H

- Source: 6x8W RGBWAP LEDs
- CT: W: 6880K
- CRI: 77
- Luminous flux: 1358.9lm
- Beam angle: 26°
- Colour mixing: RGBWAP/FC
- Colour wheel: virtual colour wheel with presets
- Sound mode: music activation through internal microphone and sensitivity control
- Protocols: DMX512
- DMX channels: 6/8/12 channel
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 46.5W
- Output (at 230V): 27 units on a single power line
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 30
- Dimensions (WxHxD): 226x164x207mm
- Weight: 2.2kg



LUMIPARIRCH
(included)

FLATPAR3H

- Source: 3x8W RGBWAP LEDs
- CT: W: 6200K
- CRI: 70
- Luminous flux: 651.27lm
- Beam angle: 25°
- Colour mixing: RGBWAP/FC
- Colour wheel: virtual colour wheel with presets
- Sound mode: music activation through internal microphone and sensitivity control
- Protocols: DMX512
- DMX channels: 6/8/10 channel
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 25.5W
- Output (at 230V): 47 units on a single power line
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 30
- Dimensions (WxHxD): 187x152x187mm
- Weight: 1.68kg



LUMIPARIRCH
(included)

FLATPAR3Q

- Source: 3x8W RGBA LEDs
- Beam angle: 25°
- Colour mixing: RGBA/FC
- Colour wheel: virtual colour wheel with presets
- Sound mode: music activation through internal microphone and sensitivity control
- Protocols: DMX512
- DMX channels: 4/9 channel
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 25W
- Output (at 230V): 30 units on a single power line
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 30
- Dimensions (WxHxD): 187x152x187mm
- Weight: 1.6kg





LUMIPARIRCH
(included)

ACCENT1Q

- Source: 1x10W RGBW LED
- Luminous flux: 279lm
- Beam angle: 10°
- Colour mixing: RGBW/FC
- Colour wheel: virtual colour wheel with presets
- Protocols: DMX512
- DMX channels: 4/6/10channel
- Power consumption (at 230V): 14,6W
- Signal connection: Seetronic XLR 5p IN/OUT connectors
- Power connection: moulded IP power IN connector
- IP rating: 30
- Dimensions (WxHxD): 110x67x172 mm
- Weight: 0.89kg

TRUSSPOD3T

- Source: 3x3.5W RGB LEDs
- Luminous flux: 321lm
- Beam angle: 16°
- Colour mixing: RGB/FC
- Colour wheel: virtual colour wheel with presets
- Sound mode: music activation through internal microphone and sensitivity control
- Protocols: DMX512
- DMX channels: 3/8 channel
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 11.4W
- Output (at 230V): 97 units on a single power line
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 30
- Dimensions (WxHxD): 121x104x108mm
- Weight: 0.65kg

