LIVEPACK1500D



LIVE12SA

Active audio system, 1 subwoofer and 2 tops, D-class bi-amp, 3-way 1000W+2x250W, 130dB

- Low frequency:15 '' woofer/3''v.c.
- Mid low frequency:2x8 '' woofer/3''v.c.
- High frequency:2x1 '' driver/1.3''v.c.
- Frequency response:50-18000 Hz (±3dB)
- Adjustable crossover: LPF:80/120 Hz - HPF 22, 80,125 Hz
- Reproduction of voice and music for live and recorded performances
- For indoor/outdoor sound installations where quality and sound pressure are required
- For portable PA systems, mobile DJ sets and voice/multimedia applications
- Birch plywood enclosure

15" 2x8" 2x1" DIGITAL AMP ANALOG PROC 80°x60° RIGGING LPF CONTROL OUT HPF

LIVE15PACK1500D TECHNICAL DATA

LOUDSPEAKERS
- System type: stereo amplified audio system

COMPONENTS
- Low frequency: 15'' woofer/4''v.c.
- Mid frequency: 2x8'' midrange / 2'' v.c.
- High frequency: 2x1'' driver/1.3''v.c.

FEATURES
- Amplified subwoofer: Built-in amp L.F. -1000 + M.H.F. 2x250W 8Ohm
- Passive mid high: 2 unit x 150W AES
- Adjustable crossover: LPF:80/200 Hz - HPF 22, 80,125 Hz

ACOUSTICAL SPECIFICATIONS
- SPL cont/peak: 114/120dB @1m (free field)
- Frequency response: 40-18000Hz (±3dB)
- Coverage angle HxV: 90x60°
- Cross over frequency: LPF:80/200 Hz - HPF 22, 80,125 Hz


ELECTRONICS
- Amplifier: digital
- Power: LF 1000 + MF/HF 2X250W /8Ohm
- Protection: limiter temp.
- User controls: mic, line, master, bal, eq LF-HF, phase, LPF, HPF
- Processor: analog
- Operating voltage/frequency: 100~120V/220~240V 60Hz/50Hz

INPUT/OUTPUT CONNECTORS
- Input signal: XLR IN/OUT, jack 6.35 mm, pin RCA unbal.
- Output signal: 2 x 4 pole
- Power connection: VDE

CABINET CONSTRUCTION
- Cabinet material: L.F.18 - M.H.15mm birchplywood
- Sospension system: eyebolt, 35 mm pole mount
- Angle: 75° unit M.H. trapezoidal taper
- Handles: L.F. unit 2 on side

PHYSICAL
- Dimensions (WxHxD): L.F. 585x450x550 - M.H. 231x420x250mm
- Weight: L.F. 40 - M.H. 2x9kg


LIVE8A / LIVE8 - Technical Drawings



Optional accessories

BAGLIVE8: Fabric protection for LIVE8/LIVE8A
AS285: Wall bracket for LIVE8/LIVE8A speakers
ACCA5460: Lifting M6 eye-bolt, suitable for suspension of loudspeakers


LIVE10A / LIVE10 - Technical Drawings



Optional accessories

BAGLIVE10: Fabric protection for LIVE10/LIVE10A
AS255: Wall mount support for acoustic speakers, horiz. & vertical, max load 60 kg
ACCA5462: M8 eye-bolt suitable for suspension of loudspeakers


LIVE12A / LIVE12 - Technical Drawings



Optional accessories

BAGLIVE12: Fabric protection for LIVE12/LIVE12A
AS255: Wall mount support for acoustic speakers, horiz. & vertical, max load 60 kg
ACCA5462: M8 eye-bolt suitable for suspension of loudspeakers

LIVE15A / LIVE15 - Technical Drawings



Optional accessories

BAGLIVE15: Fabric protection for LIVE15/LIVE15A
AS255: Wall mount support for acoustic speakers, horiz. & vertical, max load 60 kg
ACCA5462: M8 eye-bolt suitable for suspension of loudspeakers