

WIFI USB (optional)

MINIVERSAPAR

- Source: 7x10W RGBW LEDs
- Luminous flux: (10°) 1012lm (40°) 1335lm
- Lux: (10°) 4415 lux, (40°) 378lux @3m
- Zoom: 10°- 40° motorised linear zoom
- Lens type: honeycomb gapless plano-convex optics
- Colour mixing: RGBW/FC
- Colour wheel: virtual colour wheel with presets
- Protocols: DMX512
- DMX channels: 5/7/10channel
- Dimmer: linear 0~100% electronic dimmer
- Dimmer curves: different dimming curves available
- Strobe / shutter: 1/28 Hz, electronic
- Power consumption (at 230V): 69,2W
- Output (at 230V): 54 units on a single power line
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 3p+5p IN/OUT connectors
- Power connection: Seetronic powerKon IN/OUT connectors
- IP rating: 30 with a protective vent to prevent condensation, dust, compensate pressure
- Dimensions (WxHxD): 235x156x301mm
- Weight: 3.7kg



WIFIUSB (optional) LUMIPARIRCH (optional)

LUMIPAR12UH

- Source: 12x8W RGBWAP LEDs
- Luminous flux: 2537lm
- Beam angle: 25°
- Colour mixing: RGBWAP/FC
- Colour wheel: virtual colour wheel with presets
- Protocols: DMX512
- DMX channels: 6/11channel
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 83W
- Output (at 230V): 30 units on a single power line
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: variants available
- IP rating: 44
- Dimensions (WxHxD): 253x200x237mm
- Weight: 3.3kg

Variants

LUMIPAR12UH3 Power connections: IEC 3p IN/OUT

LUMIPAR12UH3P Power connections: powerCON 3p



WIFIUSB (optional) LUMIPARIRCH (optional)

LUMIPAR12UQPRO

- Source: 12x8W RGBW LEDs
- CT: W: 6600K
- Luminous flux: 3035.7lm
- Beam angle: 16°
- Colour mixing: RGBW/FC
- Colour wheel: virtual colour wheel with presets
- Protocols: DMX512
- DMX channels: 4/9channel
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 77W
- Output (at 230V): 17 units on a single power line
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: variants available
- Power connection: variants available
- IP rating: 44
- Dimensions (WxHxD): 253x200x237mm
- Weight: 3.3kg

Variants

LUMIPAR12UQPRO3 Signal connections: IEC 3p IN/OUT

LUMIPAR12UQPRO5 Signal connections: powerCON 5p IN/OUT



WIFIUSB (optional) LUMIPARIRCH (optional)

LUMIPAR12UQ

- Source: 12x4W RGBW LEDs
- Luminous flux: 1685lm
- Beam angle: 13°
- Colour mixing: RGBW/FC
- Colour wheel: virtual colour wheel with presets
- Protocols: DMX512
- DMX channels: 4/9channel
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 47W
- Output (at 230V): 27 units on a single power line
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 20
- Dimensions (WxHxD): 246x209x230mm
- Weight: 2.2kg

LUMIPACK12UQ

Lighting kit composed of 4 LUMIPAR12UQ, nylon bag, DMX/Power cables, IRC remote



WIFIUSB (optional) LUMIPARIRCH (optional)

LUMIPAR12UAW

- Source: 12x6W tunable white LEDs
- CT: WW 2600-2850 K CW 6000-6500 K ALL 1600K
- CRI: WW 82 Ra - CW 80
- Luminous flux: 1844lm
- Beam angle: 16°
- Colour mixing: tunable white
- Protocols: DMX512
- DMX channels: 3/7channel
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 61W
- Output (at 230V): 40 units on a single power line
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: variants available
- Power connection: Seetronic powerKon IN/OUT connectors
- IP rating: 44
- Dimensions (WxHxD): 253x200x237mm
- Weight: 3.3kg

Variants

LUMIPAR12UAW3 Signal connections: 3p IN/OUT

LUMIPAR12UAW5 Signal connections: 3P+5p IN/OUT



WIFIUSB (optional) LUMIPARIRCH (optional)

LUMIPAR6UQ

- Source: 6x4W RGBW LEDs
- Luminous flux: 1030lm
- Beam angle: 14°
- Colour mixing: RGBW/FC
- Colour wheel: virtual colour wheel with presets
- Protocols: DMX512
- DMX channels: 4/9channel
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 48W
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 20
- Dimensions (WxHxD): 210x173x200mm
- Weight: 1.6kg

LUMIPACK6UQ

Lighting kit composed by 4 LUMIPAR6UQ, nylon bag, DMX/ Power cables, IRC remote