



DISPLAYCOBTRWDFC

60W track mounted and WDMX FC LED fixture



LIGHT SOURCE

60W
COB RGB LED



BEAM ANGLE

60°, 30° (incl.)
15° (opt)



CONNECTIVITY

DMX512, W-DMX



IP RATING

20

DISPLAYCOBTRWDFC is the track mount version of DISPLAYCOBFC. Featuring elegant white housing and wireless DMX module on-board allowing remote control of the light making it a perfect and innovative solution for installations in commercial spaces, showrooms, museums and churches.

DISPLAYCOBTRWDFC employs 60W COB LED source RGB/FC combined with a special parabolic reflector built in aluminium which develops an extremely bright and homogeneous output and interchangeable lens systems to switch from 60°(incl.) to 30°(incl.) and 15° (opt.)

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

- Source: 60W COB RGB LED
- Luminous flux: 2055lm
- Lux: (60°) 122.7lux @3m full

OPTICS

- Beam angle: 60°
- Lens type: dichroic parabolic reflector in combination with HD fresnel lens
- Additional optics: 30° (incl.) - 15° (opt)

COLOUR SYSTEM

- Colour mixing: RGB/FC
- Colour wheel: virtual colour wheel with presets

CONTROL

- Protocols: DMX512, W-DMX
- DMX channels: 3 / 5 / 8channel
- W-DMX: included, wireless solution receiver

ELECTRONICS

- Dimmer: linear 0~100% electronic dimmer
- Dimmer curves: 4 different dimming curves available
- Strobe / shutter: 1-25 Hz, electronic
- Selectable PWM: 600~25K Hz

ELECTRICAL

- Power consumption (at 230V): 75W
- Output (at 230V): 19 units on a single power line

PHYSICAL

- Signal connection: XLR 5p IN/OUT connectors
- Power connection: track adaptor (EUTRAC, STAFF, GLOBAL, IVELA compatible)
- IP rating: 20
- Dimensions (WxHxD): 166x118x290mm
- Weight: 1.85kg



DISPLAYCOBTRWDWW

45W track mounted and WDMX warm white LED fixture



LIGHT SOURCE

45W
white COB LED



BEAM ANGLE

60°, 30° (inc)
15° (opt)



CONNECTIVITY

DMX512, W-DMX



IP RATING

20

DISPLAYCOBTRWDWW is the track mount version of DISPLAYCOBWW. Featuring elegant white housing and Wireless DMX module on-board for the remote control of the light making this a perfect solution for an innovative installation in commercial spaces, showrooms, museums and churches. DISPLAYCOBTRWDWW employs 45W COB LED source tungsten white 3200K combined with a special parabolic reflector built in aluminium which develops an extremely bright and homogeneous output and interchangeable lens systems to switch from 60° (incl.) to 30° (incl.) and 15° (opt.)

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

- Source: 45W white COB LED
- CT: 3200K
- CRI: >97
- Luminous flux: 1682lm
- Lux: (60°) 244.7lux @3m

OPTICS

- Beam angle: 60°
- Lens type: dichroic parabolic reflector in combination with HD fresnel lens
- Additional optics: 30° (inc) - 15° (opt)

CONTROL

- Protocols: DMX512, W-DMX
- DMX channels: 1 / 2 / 5channel
- W-DMX: included, wireless solution receiver

ELECTRONICS

- Dimmer: linear 0~100% electronic dimmer
- Dimmer curves: 4 different dimming curves available
- Strobe / shutter: 1-25 Hz, electronic
- Selectable PWM: 600~25K Hz

ELECTRICAL

- Power consumption (at 230V): 62W
- Output (at 230V): 24 units on a single power line

PHYSICAL

- Signal connection: XLR 5p IN/OUT connectors
- Power connection: track adaptor (EUTRAC, STAFF, GLOBAL, IVELA compatible)
- IP rating: 20
- Dimensions (WxHxD): 166x118x290mm
- Weight: 1.85kg