WIFIUSB (optional) LUMIPARIRCH (optional)

LUMIPAR12UTRI

- Source: 12x3W RGB LEDs
- Luminous flux: 1167lm
- Beam angle: 16°
- Colour mixing: RGB/FC
- Colour wheel: virtual colour wheel with presets
- Sound mode: music activation through internal microphone and sensitivity control
- Protocols: DMX512
- DMX channels: 3/8channel
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 35,5W
- Output (at 230V): 35 units on a single power line
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 20
- Dimensions (WxHxD): 226x184x220mm
- Weight: 1.8kg

LUMIPACK12UTRI

Lighting kit composed of 4 LUMIPAR12UTRI, nylon bag, DMX/power cable, IRC remote

WIFIBOX PROTOCOL

WIFIUSB (optional) LUMIPARIRCH (optional)

LUMIPAR7UTRI

- Source: 7x3W RGB LEDs
- Luminous flux: 681lm
- Beam angle: 16°
- Colour mixing: RGB/FC
- Colour wheel: virtual colour wheel with presets
- Sound mode: music activation through internal microphone and sensitivity control
- Protocols: DMX512
- DMX channels: 3/7channel
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 20W
- Output (at 230V): 57 units on a single power line
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 20
- Dimensions (WxHxD): 183x141x179mm
- Weight: 1.2kg

LUMIPACK7UTRI

Lighting kit composed of 4 LUMIPAR7UTRI, nylon bag, DMX/Power cables, IRC remote

WIFIBOX PROTOCOL

WIFIUSB (optional) LUMIPARIRCH (optional)

QUADRO18UTRI

- Source: 18x3W RGB LEDs
- Luminous flux: 2040lm
- Beam angle: 13°
- Colour mixing: RGB/FC
- Protocols: DMX512
- DMX channels: 3/5/9/13channel
- Pixel control: section control
- W-DMX: optional, proprietary protocol compatible with WIFIBOX, WDBOX
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 51.5W
- Output (at 230V): 24 units on a single power line
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 20
- Dimensions (WxHxD): 395x260x44mm
- Weight: 3.4kg

WIFIBOX PROTOCOL

FLATCOB80

- Source: 1x80W RGB LED
- Luminous flux: 1511lm
- Beam angle: 18-52°
- Colour mixing: RGB/FC
- Colour wheel: virtual colour wheel with presets
- Sound mode: music activation through internal microphone and sensitivity control
- Protocols: DMX512
- DMX channels: 3/8channel
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 56W
- Output (at 230V): 23 units on a single power line
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 20
- Dimensions (WxHxD): 200x162x230mm
- Weight: 2kg

WIFIBOX PROTOCOL

FLATCOB80UV

- Source: 1x80W UV LED
- Luminous flux: 44.5lm
- Beam angle: 16-40°
- Protocols: DMX512
- DMX channels: 1/5channel
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 65W
- Output (at 230V): 20 units on a single power line
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 20
- Dimensions (WxHxD): 200x162x230mm
- Weight: 2kg

WIFIBOX PROTOCOL

FLATCOB40

- Source: 1x40W RGB LED
- Luminous flux: 705.32lm
- Beam angle: 18-45°
- Colour mixing: RGB/FC
- Colour wheel: virtual colour wheel with presets
- Sound mode: music activation through internal microphone and sensitivity control
- Protocols: DMX512
- DMX channels: 3/8channel
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 34W
- Output (at 230V): 36 units on a single power line
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 20
- Dimensions (WxHxD): 189x151x220mm
- Weight: 1.5kg

WIFIBOX PROTOCOL