



Technical data	PL16H53
Max load	160 kg
Min load	25 kg
Max height	5.3 m
Height (folded)	1.7 m
Base area (open)	252x252 cm
Inner frame diameter	35 mm
Weight	45 kg

PL16H53

Telescopic lifter

- Made of zinc-plated steel, highly resistant to corrosion and oxidation
- · Manual winch with automatic brake allowing for a smooth and easy lift
- · Automatic safety device
- Four swivel wheels on the base for ease of transport
- Four independent stabilising legs with adjustable mounting plates
- Built-in spirit level to help maintain vertical position during installation and adjustment

Included



TLA351

Winch with auto-brake, max 350kg, compatible with TL139/TL152/PL12H40/PL16H53

Optional Accessories



PLA₁₀F₂

Support for truss fixed accessory, 29cm truss compatible



PLA12F2

Adjustable support for truss accessory, 18-59cm



PLA14B1

Light support bar with round profile, 149cm



Pole support for parallel truss accessory



Support for lighting bar accessory



Bar support for 2 acoustic boxes



Support for double bar accessory, equipped with 4 clamps

13





PL22H53

Telescopic lifter

- Made of zinc-plated steel, highly resistant to corrosion and oxidation
- Manual winch with automatic brake allowing for smooth and easy lifting
- · Automatic safety device
- Four swivel wheels on the base for ease of transport
- Four independent stabilising legs, with adjustable mounting plates
- Built-in spirit level to help maintain vertical position during installation and adjustment

Included



TLA900C

Winch with automatic brake, max 900kg, compatible RL22H63/PL22H53/PL23H65

Optional Accessories



PLA20F2

Support for truss fixed accessory, 29cm truss compatible



PLA22F2

Adjustable support for truss accessory, 18-59cm



PLA21H2

PLA23P2

Bar support for 2 acoustic boxes

Support for lighting bar accessory

PLA24B1

Light support bar with round profile, 149cm



Pole support for parallel truss accessory



Support for double bar accessory equipped with 4 clamps