



NEW

PANORAMAIPWBX

19 X 40W IP65 moving wash, beam and pixel ring effect light

PANORAMAIPWBX is a stunning IP65 high-output, LED wash light with pixel ring designed to bring the workhorse LED washlight to outdoor events. Featuring 19 of Osrams new 40W RGBW Ostar LEDs, it delivers a massive output with a huge colour range and an extensive toolkit of effects.

FEATURES

- IP65 for outdoor events
- 19 LED RGBW/FC Osram 40W + outer RGB pixel ring
- Massive 3° to 45° linear zoom range from beam to wash
- Individual pixel control with on-board FX generator for both LEDs and pixel ring for fast and precise effects
- Heat-pipe cooling system for efficient cooling with virtually no noise

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

- Source: 19x40W RGBW Osram Ostar LEDs
- Lux: (3°) 60000 lux (45°) 5010lux @3m full
- Other: Outer RGB Pixel ring with frost film

OPTICS

- Zoom: 3-45° motorised linear zoom
- Lens type: high-quality glass lens optics
- Additional optics: Diffuser on outer pixel ring

COLOUR SYSTEM

- Colour mixing: RGBW/FC
- CTC: CTC control through independent DMX channel
- Colour wheel: virtual colour wheel with presets

DYNAMIC EFFECTS

- Pixel patterns: pre-programmed dynamic and static patterns
- FX generator: adjustable foreground/background colour, index, speed, direction
- Special features: Outer RGB pixel ring with several built in customizable FX macros

BODY

- Pan angle: 540/630°
- Tilt angle: 267°

CONTROL

- Protocols: DMX512, RDM, Art-Net, W-DMX
- DMX channels: V1: 18 / 42 / 44 / 120, V2: 18 / 42 / 44 / 120 channels
- Pixel control: Pixel2Pixel control
- W-DMX: included, wireless solution receiver

ELECTRONICS

- Dimmer: linear 0~100% electronic dimmer
- Strobe / shutter: 1-30 Hz, electronic

ELECTRICAL

- Power consumption (at 230V): 661W

PHYSICAL

- Signal connection: Seetronic XLR 5p IN/OUT connectors
- Data connection: Art-Net RJ45 IN/OUT
- Power connection: Neutrik powerCON TRUE1 IN connector
- IP rating: 65 for outdoor installations
- Dimensions (WxHxD): 529x676x312mm
- Weight: 35kg



LIGHT SOURCE

19x40W RGBW Osram Ostar LEDs + Outer Pixel Ring



BEAM ANGLE

3-45° motorised linear zoom



CONNECTIVITY

DMX512, RDM, Art-Net, Pixel2Pixel control, W-DMX



IP RATING

65 for outdoor events