


# $\Omega$ Pi X 26B

OmegaPiX 26B
2.6 mm
Indoor Rental LED screen





OmegaPiX 39B

3.9 mm Indoor Rental LED screen





OmegaPiX 39T 3.9 mm

Outdoor Rental LED screen

## Mechanical/Assembly features

Curve configurations
Seamless 90° Angle
Magnetic Led Module replacement (OMEGAPIX26B only)
Climbable
Hot swapping rear panel
One man assisted assembly
Ground Stacking accessories
Fly bar for both hanging and ground stacking
Corner protection for transport

Velcro strips for gapless mounting


### **Components/Electronic features**


Premium components
Mask to ensure high reliability and improved contrast
High Refresh rate >2880Hz
LED Module with internal memory for calibration
Certified CE, EMC, UL

#### Image Quality

New Novastar A8s Receiving card
18 bit+ Greyscale
Clearview technology
Rotation enabled
RCFGX Restore, Firmware copy, Mapping
MCTRLR5 Sending fully supported









# Seamless 90° angles

Seamless 90° corners through special 45° cutter cabinets:

- 45° left cabinets: OMEGAX39C45LT, OMEGAX26C45LB
- 45° right cabinets: OMEGAX39C45RT, OMEGAX26C45RB

#### **Curve configurations**

Curve configurations both concave and convex through curving mounting plates:

- 0-10° concave (10°, 5°, 2°)
- 0-5° convex (5°, 2°)