



ΩPiX 26B


OmegaPiX 26B
2.6 mm
Indoor Rental LED screen



NEW

ΩPiX 39B

OmegaPiX 39B
3.9 mm
Indoor Rental LED screen



ΩPiX 39T

OmegaPiX 39T
3.9 mm
Outdoor Rental LED screen

Mechanical/Assembly features


Curve configurations
Seamless 90° Angle
Magnetic Led Module replacement (OMEGAPIX26B only)
Climbable
Hot swapping rear panel
One man assisted assembly
Ground Stacking accessories
Fly bar for both hanging and ground stacking
Corner protection for transport
Velcro strips for gapless mounting


Components/Electronic features


Premium components
Mask to ensure high reliability and improved contrast
High Refresh rate >2880Hz
LED Module with internal memory for calibration
Certified CE, EMC, UL

Image Quality

New Novastar A8s Receiving card
18 bit+ Greyscale
Clearview technology
Rotation enabled
RCFGX Restore, Firmware copy, Mapping
MCTRLR5 Sending fully supported







Seamless 90° angles

Seamless 90° corners through special 45° cutter cabinets:

- 45° left cabinets: OMEGAX39C45LT, OMEGAX26C45LB
- 45° right cabinets: OMEGAX39C45RT, OMEGAX26C45RB

Curve configurations

Curve configurations both concave and convex through curving mounting plates:

- 0-10° concave (10°, 5°, 2°)
- 0-5° convex (5°, 2°)